

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
26 April 2001 (26.04.2001)

PCT

(10) International Publication Number  
WO 01/29778 A1

(51) International Patent Classification<sup>7</sup>: G07B 17/00

(21) International Application Number: PCT/US00/41201

(22) International Filing Date: 17 October 2000 (17.10.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/160,112	18 October 1999 (18.10.1999)	US
60/160,491	20 October 1999 (20.10.1999)	US
60/160,703	20 October 1999 (20.10.1999)	US
60/160,563	20 October 1999 (20.10.1999)	US

(71) Applicant (for all designated States except US):  
STAMPS.COM [US/US]; Suite 1040, 3420 Ocean  
Park Boulevard, Santa Monica, CA 90405 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ENGLEBERG, Ari  
[US/US]; 9615 Wendover Drive, Beverly Hills, CA 90210  
(US). VENKAT, Girish [IN/US]; Apt. 10, 10801 Rose  
Avenue, Los Angeles, CA 90034 (US). ANANDA, Mohan  
[US/US]; 459 Lakeview Canyon Road, Westlake Village,  
CA 91362 (US). MCDERMOTT, James [US/US]; Apt.  
101; 814 4th Street, Santa Monica, CA 90403-1220 (US).

(74) Agent: TABANDEH, Raymond, R.; Christie, Parker  
& Hale, LLP, P.O. Box 7068, Pasadena, CA 91109-7068  
(US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,  
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,  
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,  
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,  
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,  
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW); Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,  
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- With international search report.
- Before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments.

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR ON-LINE VALUE-BEARING ITEM SYSTEM



(57) Abstract: An on-line value bearing item (VBI) printing system that includes one or more cryptographic modules and a secure database is disclosed. The secure database has the ability to recover data in case of a database failure and includes account balances and other information for all of the on-line value-bearing item system customers and is capable of preventing access by unauthorized users. Also, a secure communication network is in operation to prevent unauthorized access to the users' data stored in the data-base. A plurality of subsystems located on the server system side of the on-line VBI system provide services related to purchasing, accounting, and printing of VBI. Preferably, these services run on multiple server machines allowing the system to be scalable. The number of the servers can easily be increased to meet the growing needs of the subsystems as the numbers of transactions and users increase. The growing number of servers will not impact the performance of the on-line postage system, because the design of the on-line postage system allows for scalability.

WO 01/29778 A1

## METHOD AND APPARATUS FOR ON-LINE VALUE-BEARING ITEM SYSTEM

### FIELD OF THE INVENTION

The present invention relates to secure printing of value-bearing items (VBI) preferably, such as postage, tickets, and coupons. More specifically, the invention relates to a secure and recoverable on-line system for validating and printing VBI in a Wide Area Network (WAN) environment.

### BACKGROUND OF THE INVENTION

A considerable percentage of the United States Postal Service (USPS) revenue is from metered postage. Metered postage is generated by utilizing postage meters that print a special mark, also known as postal indicia, on mail pieces. Generally, printing postage and any VBI can be carried out by using mechanical meters or computer-based systems.

With respect to computer-based postage processing systems, the USPS under the Information-Based Indicia Program (IBIP) has published specifications for IBIP postage meters that identify a special purpose hardware device, known as a Postal Security Device (PSD) that is generally located at a user's site. The PSD, in conjunction with the user's personal computer and printer, functions as the IBIP postage meter. The USPS has published a number of documents describing the PSD specifications, the indicia specifications and other related and relevant information. There are also security standards for printing other types of VBIs, such as coupons, tickets, gift certificates, currency, voucher and the like.

A significant drawback of existing hardware-based systems is that a new PSD must be locally provided to each new user, which involves significant cost. Furthermore, if the additional PSD breaks down, service calls must be made to the user location. In light of the drawbacks in hardware-based postage metering systems, a software-based system has been developed that does not require specialized hardware for each user. The software-based system meets the IBIP specifications for a PSD, using a centralized server-based implementation of PSDs utilizing one or more cryptographic modules. The system also includes a database for all users' information. The software-based system, however, has brought about new challenges.

The system should also be able to handle minor and catastrophic database failures without impacting the integrity of the on-line VBI system and provide for recovery of the database to minimize or eliminate the loss of data. In a hardware-based system, security is generally handled by the local hardware piece, that is unique to each user and includes a cryptographic module that encrypts that user's information. System recovery can generally be handled by replacing the corrupted local hardware pieces for each user that stores that user's information, however, data specific to that user may be lost. Nevertheless, for a software-based system, the system need to

1 be configured to handle such database failures without sacrificing a major data loss and system security.

5 Therefore, there is a need for a new method and apparatus for implementation of an IBIP postage meter and other value-bearing items over a WAN that does not require the special purpose hardware device at the user site. Furthermore, there is a need for a secure and recoverable database in an on-line VBI system that is capable of preventing unauthorized access and handling minor and catastrophic database failures without impacting the integrity of the system.

## 10 SUMMARY OF THE INVENTION

In accordance with the present invention, a scalable on-line VBI system has been designed for printing VBI in a WAN environment that preferably meets the published USPS, and other VBI requirements. A plurality of subsystems located on the server system side of the system provide services related to purchasing, accounting, and printing of postage. Preferably, these services run on multiple server machines allowing the system to be scalable. The number of the servers can easily be increased to meet the growing needs of the subsystems as the numbers of transactions and users increase. The growing number of servers will not impact the performance of the on-line VBI system, because the design of the system allows for scalability.

20 One or more cryptographic modules are responsible for creating multiple PSDs and manipulating the PSDs data for security. The number of the cryptographic modules can also be easily increased to meet the growing needs of the system.

25 All of the transaction processing functions are performed in the servers. By locating the transaction processing functions in the servers, increases in number of transactions can easily be handled by adding additional servers. Additionally, the transactions are stateless, meaning they are not tied to one machine, so multiple server machines can service each functional subsystem allowing additional hardware to be added easily and painlessly to each subsystem in order to handle increased processing loads. Further, load balancing modules are used to distribute traffic among the various servers.

30 In addition, a schema design, in which the information containing location and format of the data is in machine-readable format, allows for data to be partitioned across multiple physical databases. The schema identifies how and where the data is located on the physical databases, therefore, it allows for the data to be partitioned across multiple physical databases. This provides for scalability as the number of users grows, because the schema can be readily updated to add new physical databases, to be spread across the database subsystem.

35 One aspect of the present invention describes a scalable on-line system for printing value bearing items (VBI) comprising: a client system for interfacing with one or more users; and a scalable server system capable of communicating with the client system over a communication network. The scalable server system includes a database remote from the users including

1 information about the users; a stateless cryptographic module for authenticating the one or more users; and a plurality of security device transaction data stored in the database for ensuring authenticity of the one or more users, wherein each security device transaction data can be processed in the server system in a stateless manner.

5 Another aspect of the present invention describes a method for printing value-bearing items (VBI) via a communication network including a client system, and a scalable server system. The method comprises the steps of: interfacing with one or more users via the client system; communicating with the client system over the communication network; storing user information in a database accessible through the network; authenticating the one or more users  
10 using a scalable cryptographic module; and storing in the database a plurality of security device transaction data for ensuring authenticity of the one or more users, wherein each security device transaction data can be processed in the server system in a stateless manner.

It is to be understood that the present invention is useful for printing not only postage, but any value bearing items, such as coupons, tickets, gift certificates, currency, voucher and the like.

#### 15 BRIEF DESCRIPTION OF THE DRAWINGS

The objects, advantages and features of this invention will become more apparent from a consideration of the following detailed description and the drawings, in which:

20 FIG. 1 is a block diagram for the client/server architecture of one embodiment of the present invention;

FIG. 2 is a block diagram of a remote user computer connected to a server via Internet;

FIG. 3 is a block diagram of one embodiment of postage servers;

FIG. 4 is a block diagram of servers, databases, and services provided by one embodiment of the present invention;

25 FIG. 4A is a block diagram of servers, databases, and services provided by one embodiment of the present invention;

FIG. 5 is a block diagram of further servers, databases, and services provided by one embodiment of the present invention;

30 FIG. 6 is a block diagram of some of the hardware components that provide security and back up to a database; and

FIG. 7 is a block diagram of a client software, a cryptographic module, and a typical transaction between them during an operational state.

#### DETAILED DESCRIPTION

35 In one aspect, the system and method of the present invention prevent unauthorized electronic access to a database subsystem and secure customers' related data, among others. One level of security is achieved by protecting the database subsystem by a postal server subsystem. The postal server subsystem controls preferably, all communications with the database subsystem

1 by executing an authentication algorithm to prevent unauthorized access. Another level of security is achieved by encrypting preferably, all communications between the client system and the postal server subsystem. The encryption-decryption function is employed using commonly known algorithms, such as, Rivest, Shamir and Adleman ("RSA") public key encryption, DES, 5 Triple-DES, Pseudo-random number generation, and the like algorithms. Additionally, DSA signature, and SHA-1 hashing algorithms may be used to digitally sign a postage indicium.

Another measure of security is the interaction between a cryptographic module and the database subsystem whenever a PSD transaction (security device transaction) is initiated. The cryptographic module and the database subsystem cross-verify the last PSD transaction (security 10 device transaction) before proceeding with the next PSD transaction. If the last transaction record in the cryptographic module and the database subsystem do not match, then the on-line VBI system shuts down until the situation can be investigated. This verification process protects against attempts of unauthorized individuals to replace the database subsystem. The registers in the cryptographic modules are cryptographically protected to achieve another level of security.

15 An exemplary on-line postage system is described in U.S. patent Application No. 09/163,993 filed September 15, 1998, the entire contents of which are hereby incorporated by reference herein. The on-line postage system includes an e protocol that operates in conjunction with the USPS requirements. The system utilizes on-line postage system software comprising user code that resides on a client system and controller code that resides on a server system. The 20 on-line postage system allows a user to print a postal indicium at home, at the office, or any other desired place in a secure, convenient, inexpensive and fraud-free manner. The system comprises a user system electronically connected to a server system, which in turn is connected to a USPS system.

Each of the cryptographic modules may be available for use by any user. When a user 25 requests a PSD service, one of the available modules is loaded with data belonging to the user's account and the transaction is performed. When a module is loaded with a user's data, that module becomes the user's PSD. The database record containing each user's PSD data is referred to as the "PSD package" (security device transaction data). After each PSD transaction is completed, the user's PSD package is updated and returned to a database external to the 30 module. The database becomes an extension of the module's memory and stores not only the items specified by the IBIP for storage inside the PSD, but also the user's personal cryptographic keys and other security relevant data items (SRDI) and status information needed for continuous operation. Movement of this sensitive data between the modules and the database is secured to ensure that PSD packages could not be compromised.

35 In one embodiment, the server system is remotely located in a separate location from the client system. All communications between the client and the server are preferably accomplished via the Internet. FIG. 1 illustrates a remote client system 220a connected to a server system 102 via the Internet 221. The client system includes a processor unit 223, a monitor 230, printer port

1 106, a mouse 225, a printer 235, and a keyboard 224. Server system 102 includes Postage servers  
109, Database 130, and cryptographic modules 110.

5 An increase in the number of servers within the server system 102 will not negatively  
impact the performance of the system, since the system design allows for scalability. The Server  
system 102 is designed in such a way that all of the business transactions are processed in the  
servers and not in the database. By locating the transaction processing in the servers, increases  
in the number of transactions can be easily handled by adding additional servers. Also, each  
transaction processed in the servers is stateless, meaning the application does not remember the  
specific hardware device the last transaction utilized. Because of this stateless transaction design,  
10 multiple servers can be added to each appropriate subsystem in order to handle increased loads.

Furthermore, each cryptographic module is a stateless device, meaning that a PSD package  
can be passed to any device because the application does not rely upon any information about  
what occurred with the previous PSD package. Therefore, multiple cryptographic modules can  
also be added to each appropriate subsystem in order to handle increased loads. A PSD package  
15 for each cryptographic module is a database record, stored in the server database, that includes  
information pertaining to one customer's service that would normally be protected inside a  
cryptographic module. The PSD package includes all data needed to restore the PSD to its last  
known state when it is next loaded into a cryptographic module. This includes the items that the  
IBIP specifications require to be stored inside the PSD, information required to return the PSD  
20 to a valid state when the record is reloaded from the database, and data needed for record security  
and administrative purposes.

In one embodiment, the items included in a PSD package include ascending and  
descending registers (the ascending register "AR" records the amount of postage that is dispensed  
or printed on each transaction and the descending register "DR" records the value or amount of  
25 postage that may be dispensed and decreases from an original or charged amount as postage is  
printed.), device ID, indicia key certificate serial number, licensing ZIP code, key token for the  
indicia signing key, the user secrets, key for encrypting user secrets, data and time of last  
transaction, the last challenge received from the client, the operational state of the PSD,  
expiration dates for keys, the passphrase repetition list and the like.

30 As a result, the need for specific PSDs being attached to specific cryptographic modules  
is eliminated. A Postal Server subsystem provides cryptographic module management services  
that allow multiple cryptographic modules to exist and function on one server, so additional  
cryptographic modules can easily be installed on a server. The Postal Sever subsystem is easy  
to scale by adding more cryptographic modules and using commonly known Internet load-  
balancing techniques to route inbound requests to the new cryptographic modules.  
35

Referring back to FIG. 1, Postage servers 109 include one or more Postal servers and  
provide indicia creation, account maintenance, and revenue protection functionality for the  
exemplary on-line postage system. The Postage servers 109 may include several physical servers

1 in several distinct logical groupings, or services as described below. The individual servers could be located within one facility, or in several facilities, physically separated by great distance but connected by secure communication links.

5 Cryptographic modules 110 are responsible for creating PSDs and manipulating PSD data to protect sensitive information from disclosure, generating the cryptographic components of the digital indicia, and securely adjusting the user registration. When a user wishes to print VBI, for example, postage or purchase additional VBI or postage value, a user state is instantiated in the PSD implemented within one of the cryptographic modules 110. Database 111 includes all the data accessible on-line for indicia creation, account maintenance, and revenue protection processes. Postage servers 109, Database 130, and cryptographic modules 110 are maintained  
10 in a physically secured environment, such as a vault.

FIG. 2 shows a simplified system block diagram of a typical Internet client/server environment used by an on-line VBI system in one embodiment of the present invention. PCs 220a-220n used by the postage purchasers are connected to the Internet 221 through the communication links 233a-233n. Each PC has access to one or more printers 235. Optionally,  
15 as is well understood in the art, a local network 234 may serve as the connection between some of the PCs, such as the PC 220a and the Internet 221 or other connections. Servers 222a-222m are also connected to the Internet 221 through respective communication links. Servers 222a-222m include information and databases accessible by PCs 220a-220n. The on-line VBI system  
20 of the present invention resides on one or more of Servers 222a-222m.

In this embodiment, each client system 220a-220m includes a CPU 223, a keyboard 224, a mouse 225, a mass storage device 231, main computer memory 227, video memory 228, a communication interface 232a, and an input/output device 226 coupled and interacting via a communication bus. The data and images to be displayed on the monitor 230 are transferred first  
25 from the video memory 228 to the video amplifier 229 and then to the monitor 230. The communication interface 232a communicates with the servers 222a-222m via a network link 233a. The network link connects the client system to a local network 234. The local network 234 communicates with the Internet 221.

In one embodiment, a customer, preferably licensed by the USPS and registered with an IBIP vendor (such as Stamps.com), sends a request for authorization to print a desired amount  
30 of VBI, such as postage. The server system verifies that the user's account holds sufficient funds to cover the requested amount of postage, and if so, grants the request. The server then sends authorization to the client system. The client system then sends image information for printing of a postal indicium for the granted amount to a printer so that the postal indicium is printed on  
35 an envelope or label.

In one embodiment, when a client system sends a VBI print request to the server system, the request needs to be authenticated before the client system is allowed to print the VBI, and while the VBI is being printed. The request is cryptographically authenticated using an

1 authentication code. The client system sends a password (or passphrase) entered by a user to the  
server for verification. If the password fails, a preferably asynchronous dynamic password  
verification method terminates the session and printing of the VBI is aborted. Also, the server  
5 system communicates with a system located at a certification authority for verification and  
authentication purposes.

In one embodiment, the information processing components of the on-line VBI system  
include a client system, a postage server system located in a highly secure facility, a USPS system  
and the Internet as the communication medium among those systems. The information  
processing equipment communicates over a secured communication line.

10 Preferably, the security and authenticity of the information communicated among the  
systems are accomplished on a software level through the built-in features of a Secured Socket  
Layer (SSL) Internet communication protocol. An encryption hardware module embedded in the  
server system is also used to secure information as it is processed by the secure system and to  
ensure authenticity and legitimacy of requests made and granted.

15 The on-line VBI system is based on a client/server architecture. Generally, in a system  
based on client/server architecture the server system delivers information to the client system.  
That is, the client system requests the services of a generally larger computer. In one  
embodiment, the client is a local personal computer and the server is a more powerful group of  
computers that house the information. The connection from the client to the server is made via  
20 a Local Area Network, a phone line or a TCP/IP based WAN on the Internet or any other types  
of communication links such as wireless or satellite links. A primary reason to set up a  
client/server network is to allow many clients access to the same applications and files stored on  
the server system.

25 The on-line VBI system does not require any special purpose hardware for the client  
system. The client system is implemented in the form of software that can be executed on a user  
computer (client system) allowing the user computer to function as a virtual VBI meter. The  
software can only be executed for the purpose of printing the VBI indicia when the user computer  
is in communication with a server computer located, for example, at a VBI meter vendor's  
facility (server system). The server system is capable of communicating with one or more client  
30 systems simultaneously.

In one embodiment, the on-line system includes the following subsystems: the Database  
subsystem, the Postal Server subsystem, the Provider Server subsystem, the E-commerce  
subsystem, the Staging subsystem, the Client Support subsystem, the Decision Support  
subsystem, the SMTP subsystem, the Address Matching service (AMS) subsystem, the SSL  
35 Proxy Server subsystem and the Web Server subsystem, and the like, as shown in FIGs. 4 and  
4A. Preferably, the Database, Postal Server, Provider, E-commerce, Client Support Services,  
SMTP, AMS, SSL Proxy Server, Web Server subsystems, and Staging subsystems reside in the  
vault while the Decision Support Services reside outside the vault.



1 Postage servers 109 in FIG. 1 include a string of servers connected to the Internet, for  
example, through a T1 line, and are preferably protected by a firewall. The firewall permits a  
client to communicate with a server system, only if the information packet transmitted by the  
client system complies with a security policy set by the server system. The firewall not only  
5 protects the system from unauthorized users on the Internet, it also separates the Public Network  
(PUBNET) from the Private Network (PRVNET). This ensures that packets from the Internet  
will not go to any location but the PUBNET. The string of servers form the different subsystems  
of the postal system. The services provided by the different subsystems of the on-line VBI  
system are designed to allow flexibility and expansion and reduce specific hardware dependancy.

10 The Database subsystem is comprised of multiple databases. FIG. 4 illustrates an  
exemplary Database subsystem which includes the Postal Database 47, Postal Database  
Management System 47A, the Provider Database 42, Provider Database Management System  
42A, the E-commerce Database 46, E-commerce Database Management System 46A, the  
Membership Database 48, the Membership Database Management System 48A, the Staging  
15 Services Database 49, and the Staging Services Database Management System 49A protected by  
firewall 40. Different portions of the Database subsystem are described below. Also, the  
databases are referred to as a portion of the Database subsystem after an initial reference as the  
subsystem database (e.g., Postal Database first, then Postal portion of the Database subsystem).  
A secure standby backup database server (not shown) mirrors the primary database server to  
20 minimize the impact of any interruption of the primary database server.

The Postal Server subsystem 41 manages client and remote administration access to server  
functionality, authenticates clients and allows clients to establish a secure connection to the on-  
line VBI system. The Postal Server subsystem also manages access to USPS specific data such  
as PSD information and a user's license information. The Postal Server subsystem queries the  
25 Postal portion of the Database subsystem for the necessary information to complete the task. The  
query travels through the firewall 40 to the Postal portion of the Database subsystem. The Postal  
Server subsystem is the subsystem in the Public Network that has access to the Database  
subsystem.

In one embodiment, the Database subsystem is comprised of multiple databases, as shown  
30 in FIG. 4A. In this embodiment, the Database 411 includes the Affiliate DBMS and the Source  
IDs DBMS. The Affiliate DBMS manages affiliate information (e.g., affiliate's name, phone  
number, and affiliate's Website information) that is stored on the Affiliate Database. Using the  
data from this database, marketing and business reports are generated. The Source IDs Database  
contains information about the incoming links to the vendor's Website (e.g., partners'  
35 information, what services the vendor offers, what marketing program is associated with the  
incoming links, and co-branding information). Using the data from this database, marketing and  
business reports are generated.

1       The Online Store Database 412 contains commerce product information, working orders,  
billing information, password reset table, and other marketing related information. Website  
database 410 keeps track of user accesses to the vendor website. This database keeps track of  
5       user who access the vendor website, users who are downloading information and programs, and  
the links from which users access the vendor website. After storing these data on the Website  
Database 410, software tools are used to generate the following information:

- Web Site Status
- Web Site Reports
- Form Results
- 10      •       Download Successes
- Signup, Downloads, and Demographic Graphs
- Web Server Statistics (Analog)
- Web Server Statistics (Web Analyzer)

15       Offline database 409 manages the VBI data (except meter information), postal transactions  
data, financial transactions data (e.g., credit card purchases, free postage issued, bill credits, and  
bill debits), customer marketing information, commerce product information, meter license  
information, meter resets, meter history, and meter movement information. Consolidation Server  
413 acts as a repository for data, centralizing data for easy transportation outside the vault 400.  
20       The Consolidation Server hosts both file and database services, allowing both dumps of activity  
logs and reports as well as a consolidation point for all database data.

25       The Offline Reporting Engine MineShare Server 415 performs extraction transformation  
from the holding database that received transaction data from the Consolidated Database  
(Commerce database 406, Membership database 408, and Postal Database 407). Also, the  
Offline Reporting Engine MineShare Server handles some administrative tasks. Transaction data  
30       in the holding database contains the transaction information about meter licensing information,  
meter reset information, postage purchase transactions, and credit card transactions. After  
performing extraction transformation, business logic data are stored on Offline Database 409.  
Transaction reports are generated using the data on the Offline Database. Transaction reports  
contain marketing and business information.

35       The Data Warehouse database 414 of FIG. 4A includes all customer information, financial  
transactions, and aggregated information for marketing queries (e.g., how many customers have  
purchased postage). In one embodiment, commerce Database 406 includes a Payment Database,  
an E-mail Database, and a Stamp Mart Database. The E-mail DBMS manages access to the  
contents of e-mail that were sent out to everyone by vendor servers. The Stamp Mart database  
handles order form processing. The E-commerce Server 404 provides e-commerce related  
services on a user/group permission basis. It provides commerce-related services such as  
payment processing, pricing plan support and billing as well as customer care functionality and  
LDAP membership personalization services.

1 A Credit Card Service is invoked by the E-commerce Server 404 to authorize and capture funds from the customer's credit card account and to transfer them to the vendor's merchant bank. A Billing Service is used to provide bills through e-mail to customers based on selected billing plans. An ACH service runs automatically at a configurable time. It retrieves all pending  
5 ACH requests and batches them to be sent to bank for postage purchases (i.e. money destined for the USPS), or Chase for fee payments which is destined for the vendor account.

The E-commerce DBMS 406 manages access to the vendor specific Payment, Credit Card, and Email Databases. A Membership DBMS manages access to the LDAP membership directory database 408 that hosts specific customer information and customer membership data. A Postal  
10 DBMS manages access to the Postal Database 407 where USPS specific data such as meter and licensing information are stored. A Postal Server 401 provides secure services to the Client, including client authentication, postage purchase, and indicia generation. The Postal Server requires cryptographic modules to perform all functions that involve client authentication, postage purchase, and indicia generation.

15 Postal Transaction Server 403 provides business logic for postal functions such as device authorization and postage purchase/register manipulation. The Postal Transaction Server requires the cryptographic modules to perform all functions. There are four Client Support Servers. Address Matching Server (AMS) 417 verifies the correct address specified by a user. When the user enters a delivery address or a return address using the Client Software, the user does not  
20 need the address matching database on the user's local machine to verify the accuracy of the address. The Client software connects to the vendor's server and uses the central address database obtained from the USPS to verify the accuracy of the address. If the address is incorrect, the client software provides the user with a prioritized list of addresses to match the correct address. These choices are ranked in a user definable order. This information is  
25 represented using a plain text format.

The Client Support Servers 417 of FIG. 4A provides the following services: a Pricing Plan service, an Auto Update service, and a Printer Config service. The Pricing Plan Service provides information on pricing plans and payment methods available to the user. It also provides what credit cards are supported and whether ACH is supported. This information is represented  
30 preferably using a plain text format. The Auto Update Service verifies whether the user is running the latest Client Software. If there is newer Client Software, the Auto Update Server downloads the new patches to the user computer. The Client Support Database has tables for the client software update information. This information is represented using a plain text format.

35 Before the user tries to print postage, the user sends his or her printer driver information over the Internet in plain text. The Printer Config Service looks up the printer driver information in the Printer Driver Database to determine whether the printer driver is supported or not. When the user tries to configure the printer, the user prints a test envelope to test whether the postage

1 printing is working properly or not. This testing envelope information is sent over the Internet in plain text and is stored in the Client Support Database.

5 MeterGen server 422 makes calls into the cryptographic module to create sufficient meters to ensure that the vendor can meet customer acquisition demands. SMTP Server 418 communicates with other SMTP servers, and it is used to forward e-mail to users. Gatekeeper Server works as a proxy server by handling the security and authentication validation for the smart card users to access customer and administration information that reside in the vault.

10 The Proxy Server 423 uses the Netscape™ Enterprise SSL library to provide a secure connection to the vault 400. Audit File Server 419 acts as a repository for module transaction logs. The Audit File Server verifies the audit logs that are digitally signed. The audit logs are verified in real time as they are being created. Postal Server writes audit logs to a shared hard drive on the Audit File Server. After these logs are verified, the Audit File Server preferably moves them from the shared hard drive to a hard drive that is not shared by any of the vendor servers.

15 Provider Server provides reporting and external communication functionality including the following services. CMLS Service forwards license applications and it processes responses from CMLS. The CMLS Service uses cryptographic functions provided by the Stamps.com Crypt library to decrypt the user's SSN/Tax ID/Employee ID. CMRS Service reports meter movement and resetting to the USPS Computerized Meter Resetting infrastructure. ACH Service is responsible for submitting ACH postage purchase requests to the USPS lockbox account at the bank. The CMLS Service uses cryptographic functions to decrypt the user's ACH account number.

20 After decrypting ACH account information, the ACH is encrypted using the vendor's script-library. Then, the encrypted ACH file is e-mailed to the Commerce Group by the SMTP server. When the Commerce Group receives this encrypted e-mail, the vendor's Decrypt utility application is used to decrypt the ACH e-mail. After verifying the ACH information, the Commerce Group sends the ACH information through an encrypted device first and then uses a modem to upload the ACH information to a proper bank. The Certificate Authority issues certificates for all IBIP meters. The certificates are basically used to provide authentication for indicia produced by their respective meters.

30 The following are exemplary steps describing the certificate authorization process:

- MeterGen asks the module to create a meter package,
- The module returns a package and the meter's public key,
- MeterGen creates a certificate request with the public key, signs the request with a USPS-issued smartcard, and submits the request to the USPS Certificate Authority,
- The Certificate Authority verifies the request came from the vendor then, it creates a new certificate and returns it to MeterGen.

- 1 • MeterGen verifies the certificate using the USPS Certificate Authority's certificate (e.g., to ensure it wasn't forged) and stores the certificate information in the package. The package is now ready to be associated with a customer.

5 The Postal Server subsystem 401 of FIG. 4A manages client and remote administration access to server functionality, authenticates clients and allows clients to establish a secure connection to the on-line VBI system. The Postal Server subsystem also manages access to USPS specific data such as PSD information and a user's license information. The Postal Server subsystem queries the Postal portion of the Database subsystem for the necessary information to complete the task. The query travels through the firewall to the Postal portion of the Database subsystem. The Postal Server subsystem is the subsystem in the Public Network that has access to the Database subsystem.

10 In one embodiment of the present invention, Postal Server 401 is a standalone server process that provides secure connections to both the clients and the server administration utilities, providing both client authentication and connection management functionality to the system. Postal Server 401 also houses postal-specific services that require high levels of security, such as purchasing postage or printing indicia. Postal Server 401 is comprised of at least one server, and the number of servers increases when more clients need to be authenticated, are purchasing postage or are printing postage indicia.

15 In one embodiment, as illustrated in FIG. 3, the Postal Server subsystem 41 is physically comprised of at least one cryptographic module 52, at least one Postal Server 53 and at least one PostalX Server (PSX) 54. When the workload is increased, the number of each of these devices can be increased to accommodate the additional work.

20 In one embodiment of the present invention, the cryptographic modules 52 are FIPS 140-1 certified hardware cards that include firmware to implement PSD functionality in a cryptographically secure way. The cryptographic modules are inserted into any of the servers in the Postal Server Infrastructure. The cryptographic modules are responsible for creating PSDs and manipulating PSD data to generate and verify digitally signed indicia. Since the PSD data is created and signed by a private key known only to the card, the PSD data may be stored externally to the cryptographic modules without compromising security.

25 In one embodiment of the present invention, Postal Server 53 is a standalone server process that provides secure connections to both the clients and the server administration utilities, providing both client authentication and connection management functionality to the system. Postal Server 53 also houses postal-specific services that require high levels of security, such as purchasing postage or printing indicia. Postal Server 53 is comprised of at least one server, and the number of servers increases when more clients need to be authenticated, are purchasing postage or are printing postage indicia.

30 The growth in the number of servers of the Postal Server will not impact the performance of the system since the system design allows for scalability. The Postal Server is designed in

1 such a way that all of the business logic is processed in the servers and not in the database. By  
locating the transaction processing in the servers, increases in the number of transactions can be  
easily handled by adding additional servers. Also, since each transaction is stateless (the  
application does not remember the specific hardware device the last transaction utilized),  
5 multiple machines can be added to each subsystem in order to handle increased loads. In one  
embodiment, load balancing hardware and software techniques are used to distribute traffic  
among the multiple servers.

In one embodiment of the present invention, PXS 54 is a standalone server process that  
provides trusted plain-text access to in-vault components. PXS 54 hosts postal-specific services  
10 that are protected from access external to the vault via a firewall. The PostalX Services provide  
business logic for postal functions such as device authorization and postage purchase/register  
manipulation. The PXS services require cryptographic modules to perform all functions because  
the PXS services are vital to the system's integrity and are protected by encryption. The PXS  
services can be located on one physical server or multiple machines depending on the number  
15 of postal-specific transactions.

The growth in the number of servers of the PostalX Server will not impact the  
performance of the system since the system design allows for scalability in two ways. the  
PostalX Server is designed in such a way that all of the business logic is encapsulated in the  
servers, not in the database. By locating the transaction processing in the servers, increases in  
20 the number of transactions can be easily handled by adding additional servers. Also, since each  
transaction is stateless, multiple machines can be added to each subsystem in order to handle  
increased loads. In one embodiment, load balancing hardware and software techniques are used  
to distribute traffic among the multiple servers.

Referring back to FIG. 4, the Postal Database Management System 47A manages access  
25 to the Postal section of the Database subsystem where USPS specific data such as meter and  
licensing information is stored. The Postal Database Management System is scalable and can  
be expanded to meet the needs of the Postal Server subsystem. The database schema design  
allows for the data to be partitioned across multiple physical databases. In one embodiment of  
the invention, the database is managed by relational database management software, such as MS  
30 SQL Server or the like. In one embodiment, the Postal Database Management System runs on  
two hardware servers.

The Postal Database 47 is a secure database that stores all information for the Postal  
Server subsystem. The Postal portion of the Database subsystem contains the postal-specific  
information such as licensing, registration, and meter-specific data for all of the customers.  
35 Access to the Postal portion of the Database subsystem occurs through the Postal Server  
subsystem. Each piece of client software has a unique software serial number, which will be  
generated and kept in the database during product registration.

1        Provider subsystem 42B provides reporting and external communication functionality for  
the Postal Information System. Preferably, the Provider subsystem is located on the PRVNET  
along with the Database Subsystem and communicates directly with the Database Subsystem  
when the Provider Subsystem services request Database subsystem information. As shown in  
5        FIG. 3, Provider Subsystem 42B includes Provider Server 55 and Provider Database 42. The  
Provider Subsystem 42B includes the following services: Central Metering License Services  
(CMLS), Central Meter Resetting Services (CMRS), Automated Clearing House (ACH)  
transactions, Credit Card services and Billing services. In one embodiment the Provider  
subsystem 42B runs on two hardware servers as shown in FIG. 4.

10        The CMLS service forwards license applications to and processes requests from the  
CMLS in the USPS through a CMLS/CMRS communication link. The CMRS service provides  
meter movement and meter resetting information through the CMLS/CMRS communication link  
to the USPS Computerized Meter resetting infrastructure. The ACH Service submits ACH  
15        postage purchase requests through an ACH communication link to a USPS lockbox account at  
a bank. The Credit Card Service is invoked by the E-commerce services to authorize and capture  
funds from the customer's credit card account and transfer them to a designated merchant bank.  
The Billing Service provides bills through e-mail to customers based on selected billing plans.  
All of the Provider subsystem's communication with external devices is secure, since the  
communication is encrypted.

20        The services included in the Provider subsystem 42B are classified as either services  
running across multiple servers or Singleton services. A Singleton service is a service where only  
one effective instance is executing at one time, so multiple operations of the service will not be  
operating at the same time. Preferably, the CMLS, CMRS and ACH services are all Singleton  
services and are not scalable because they transmit data in a specific format at specified times to  
25        external USPS or banking systems. The remaining services in the Provider subsystem (Credit  
Card and Billing services) are scalable and can be run on multiple servers.

30        The Provider Database Management System 42A manages access to the Provider section  
of the Database subsystem where Provider specific data such as Meter resetting records, Postage  
Value Download (PVD) information, batch status information and CMLS license information  
is stored. The PVD information is included in the log file that is sent to the USPS on a regular  
basis. The Provider Database Management Services are scalable and can be expanded to meet  
the needs of the Provider Server subsystem. The schema design allows for the data to be  
partitioned across multiple physical databases. In one embodiment, the Provider Database  
Management System runs on two hardware servers.

35        The Provider Database 42 is a secure database that stores all information for the Provider  
Server subsystem. The Provider portion of the Database subsystem contains Provider subsystem  
specific data such as Meter resetting records, PVD information, batch status information and  
CMLS license information.

1       The E-commerce subsystem 46B, shown in FIG. 3, provides functionality for the E-commerce related services required by Customer Support personnel and system administrators. The Customer Support personnel and system administrators access the on-line postage system through the E-commerce subsystem. E-commerce subsystem 46B communicates with the Database subsystem through the Postal Server subsystem and preferably is connected to a Public Network. The E-Commerce subsystem also provides commerce-related services, such as payment processing, pricing plan support and billing, as well as customer care functionality and Lightweight Directory Access Protocol (LDAP) membership personalization services.

5       LDAP is a protocol for accessing online directory services over the TCP/IP network protocol and can be used to access standalone LDAP directory services or directory services supporting the X.500 standard. It provides a standard way for Internet clients, applications and Web servers to access directory listings of large number of Internet users.

10       E-Commerce subsystem 46B also includes a group of servers and databases including the Proxy Services 43, E-commerce Servers 44, E-commerce Database 46, Membership Database 48, E-commerce Database Management System 46A, Membership Database Management System 48A, and Credit Card Server 45.

15       Proxy Services 43 provide Customer Support and authenticated access for administrators to the E-Commerce Servers. In one embodiment, the Proxy Services run on one hardware server. The E-commerce Services, such as payment processing, pricing plan support, billing, customer care functionality and LDAP membership services run on the E-commerce Servers 44. The number of the E-commerce servers can easily be increased to meet the growing needs of the E-commerce subsystem. The growing number of servers will not impact the performance of the on-line postage system because the system design allows for scalability of the servers.

20       E-commerce Database Management System 46A manages access to E-commerce Database 46 where commerce related information is stored, as shown in FIG. 4. E-Commerce Database 46 includes information on non-postal commerce transactions, credit card validations, customer invoicing, etc. E-commerce Database Management System 46A is scalable and may easily be expanded to meet the needs of the system. If the number of E-commerce related transactions increase, the database schema design allows for the data to be partitioned across additional physical databases. The schema can be easily updated to add new devices and incorporate them into the Database subsystem. In one embodiment, the E-commerce Database Management System is resident on two hardware servers. The E-commerce portion of the Database subsystem includes specific data such as purchase transactions, pricing plans, billing information, and customer account information.

25       Membership Database Management System 48A provides access to Membership database 48. The Membership Database Management System manages access to the LDAP membership directory database that hosts specific customer information and customer membership data. The Membership Database contains all customer and internal user profile information, plus security



1 information for all internal system users. The Membership Database Management System is  
scalable and expands to meet the needs of the system. If the number of customer profile  
transactions increase, the database schema design allows for the data to be partitioned across  
additional physical databases. The schema can be easily updated to add new devices and  
5 incorporate them into the Database subsystem. In one embodiment, Membership Database  
Management System 48A is resident on two hardware servers. The Membership portion of the  
Database subsystem includes specific customer profile information.

The SSL Proxy server (part of Proxy 43) allows secure HTTP access from a web browser  
and is used by the system administrators to access the e-commerce subsystem. Web Server 56A  
10 is used to maintain the website, facilitate the customer support activities and distribute the client  
software to interested parties. Web Server 56A communicates with the clients 58 through the  
Internet 221 and the internal departments via the Intranet LAN 40A. The information for  
maintaining the website and tracking affiliate performance is located in Website Database 56.  
An Affiliate Database (not shown) stores client software versions, affiliate profiles and tracking  
15 codes and Advertising and Marketing tracking numbers.

FIG. 5 illustrates more subsystems of the exemplary on-line postage system, namely, AMS  
servers 61, Client Support Servers 62, Client Support Database Management System 62A, Client  
Support Database 62B, the Decision Support Services (DSS) Database Management System 63A,  
DSS database 63, Staging Database Management System 66A and Staging Database 66, SMTP  
20 server 65, and Backup Services 65.

SMTP server 65 runs the internal and external E-mail systems. The Staging Services  
subsystem coordinates aggregation of business data. Preferably, each night, all of the changes  
made in the Database subsystem in the last 24 hours are loaded into Staging Database 66.  
Staging Services Database Management System 66A manages access to Staging Database 66.  
25 After gathering changes in the databases, Staging Services Database Management System 66A  
strips out all of the critical data such as credit card numbers and critical USPS specific  
information, and moves the changes to offline databases. Staging Services Database  
Management System 66A is scalable and may be easily be expanded to meet the needs of the  
system. In one embodiment, the Staging Services Database Management System is resident on  
30 two hardware servers.

Backup Services subsystem 64 provides the data backup for the Database subsystem. The  
first backup is the secondary Database Server, which is a live standby server that mirrors the  
primary Database server as described above. The second backup is a transaction log on the  
Postal Server that is stored (off-loaded) preferably every couple of minutes in a tape backup  
35 device, which allows the system administrators to reconstruct the system up to the last  
transactions if a database failure occurs. Finally, the entire Database subsystem is backed up  
every day and archived off premises to ensure that the data is available if the physical on-line VBI  
system suffers catastrophic failure.

1       The AMS subsystem 61 validates source and destination addresses against a USPS table  
to verify the mail is being sent to a recognized location. This service is utilized each time the  
user attempts to print postal indicia. The AMS system is used when a user enters a delivery  
address or a return address using the client software. The user does not need the address  
5       matching database on the user's local machine to verify the accuracy of the address. The client  
software connects to the Postage Server and uses a central address database obtained from the  
USPS to verify the accuracy of the address. If the address is incorrect, the client software  
provides the user with a prioritized list of addresses to match the correct address. Preferably,  
these choices are ranked in order according to the type of match.

10       Since the printing of VBI indicia is the most common transaction in this system, this  
service is separated from other services in order to ensure the AMS does not create performance  
problems in the on-line VBI system. All of the services, except for the previously-mentioned  
Singleton services, are scalable and are modified to adjust to the number of transactions  
requested. AMS transactions increase substantially when more individuals utilize the system so  
15       the AMS transactions are scaled separately from the other transactions. Preferably, load  
balancing services are used to assist distributing the workload to the AMS servers. In one  
embodiment, the AMS Services run on two servers.

20       The Client Support Services subsystem 58 of FIG. 3 is comprised of the client services  
that typically do not require secure transactions. Client Support Services subsystem 58 of FIG.  
3 includes the Client Support Servers 62, the Client Support Database Management System 62A,  
and the Client Support Database 62B, as shown in FIG 5. The services that execute on the Client  
Support Servers preferably include, Registration Services, Auto-Update Service, Printer Config  
Service, Postal Rate Info Service, and Printer DB Update Service. The Client Support Services  
are typically low in volume, however, the number of servers and the capacity of the database can  
25       be readily scaled according to the workload of the system. In one embodiment, the Client  
Support Services are run on two servers.

30       The Registration Services includes supported payment type and billing plan information.  
The Auto-Update Service updates the client software when new client software versions are  
released. The Printer Configuration Services assist in setting up the printer to guarantee that the  
indicia printed meets USPS criteria. The Rates Service calculates the correct rate for the client  
based on class, destination and weight. The Printer Database Service updates the on-line VBI  
system with any new printer or printing information.

35       The Client Support Database Management System 62A of FIG. 5 manages access to the  
Client Support Database (CSD) 62B. The processing requirements of CSD 62B are low, but  
availability of the CSD is vital, so multiple physical servers running in a cluster are necessary to  
ensure this availability. In one embodiment, the Client Support Database Management System  
runs on two hardware servers connected to one external CSD storage devices.

1 CSD 62B is an external storage component for the Client Support Services subsystem 58. Transactions executing on the Client Support Servers requiring storage utilize the CSD 62B. The data storage size requirements for CSD 62B are relatively low. As the number of Client Support Services transactions grows, the database will grow. The database schema design allows for the  
5 data to be partitioned across multiple physical databases.

The Decision Support System (DSS) includes the DSS Database Management System 63A and the DSS Database 63, as shown in FIG. 5. The DSS allows restricted (read-only, time delayed) access to the postal data. The DSS Database Management System 63A controls access to DSS Database 63. In one embodiment, the DSS various accounting tasks for the Staging  
10 Services Database Management System. As the processing requirements of the DSS vary, the availability of the DSS subsystem may also vary. Therefore, DSS Database Management System 63A runs in a cluster on multiple servers to ensure DSS availability. DSS Database 63 is preferably offline and includes most or all of the user's profile information. Preferably, Staging Database 66 receives a nightly automatic delta update, which gathers all of the data that  
15 has changed over the previous 24 hours. The data that has changed over the last 24 hours is filtered according to data access guidelines. The data is transferred from Staging Database 66 to DSS Database 63. The update is a one-way update only. After the data has been moved, it is available for reading and queries for the Marketing, Finance, Customer Support and Management departments. DSS Database 63 contains user profile information, including historical transaction  
20 information. As the number of DSS transactions grows, DSS Database 63 grows to accommodate the additional transactions. A database schema design allows for the data to be partitioned across multiple physical databases.

The on-line VBI system is designed to prevent unauthorized electronic access to the Database subsystem. FIG. 6 illustrates the hardware components that provide the security to the  
25 Database subsystem. The first line of defense is firewall 40, which prevents unauthorized access to the servers. Firewall 40 is connected to Public Network 73 and Private Network 72. Router 71A and switch 71B direct data from Internet 221 to firewall 40 and together, serve as the portal from the Internet 221 to the on-line VBI system servers. Stack Hubs 74A and 74B interface Public Network 73 and Private Network 72 to the firewall 40 respectively. Connected to  
30 Public Network 73 through Stack Hub 74A are Postal Server subsystem 41 and E-commerce subsystem 46B. Cryptographic module 52 is connected to Postal Server subsystem 41. Connected to Private Network 72 through Stack Hub 74B are Provider subsystem 42B, a Back up database 76 that mirrors information as data is stored, and the primary database 51. A tape back up system 75 is connected to primary database 51 for periodically backing up the database.

35 The second line of defense is the protection of the Database subsystem by the Postal Server Subsystem. The Public Network 73 includes the E-commerce subsystem 46B and the Postal Server subsystem 41. The Private Network 72 includes the Database subsystem 51 and the Provider subsystem 42B. The firewall 40 is configured to deny access to the Private Network

1 72 by unauthorized users. The only access to the Private Network 72 (specifically the Database  
subsystem 51) by external users is through the firewall 40. In the Public Network 73, the Postal  
Server subsystem 41 controls access to the Private Network 72. In one embodiment, dual Cisco  
PIX 520 hardware firewalls including two independent Network Interface Cards (NIC) are used  
5 for firewall 40.

The Postal Server subsystem 41 executes an authentication algorithm for dynamically and  
asynchronously verifying passwords to ensure that only properly authenticated users are allowed  
access to the Database subsystem 51. The Postal Server subsystem 41 runs software built around  
the authentication algorithm, and thus acts as a gatekeeper to prohibit unauthorized users from  
10 entering the Postal Server subsystem 41 and the Database subsystem 51. Preferably, only the  
custom made software built around the authentication algorithm runs on the Postal Server  
subsystem 41 for security purposes.

Information in the Database subsystem 51 can be retrieved or altered only by accessing  
the database through the Postal Server subsystem 41. However, the authentication algorithm  
15 executed by the Postal Server subsystem 41 prevents unauthorized access to the Database  
subsystem 51 resulting in secure information in the Database subsystem. Preferably, the E-  
Commerce subsystem 46B, also, only communicates with the Database subsystem 51 through  
the Postal Server subsystem 41. The Provider subsystem 42B communicates with the Database  
subsystem 51 directly through the Private Network 72.

20 The communications between the cryptographic modules and the Postal Server subsystem  
are secured and authenticated through a security protocol. This protocol includes two distinct  
states. The first state is the registration/authorization state that is a one-time only (per user) state  
in which the client software and each cryptographic module preferably cooperate in establishing  
two shared secrets: a user secret (e.g., a password) and a hashed message authentication key  
25 (HMK). The second state is the operational state that follows a successful completion of the  
registration/authorization state. The operational state is the normal transaction state for client  
software and each cryptographic module.

In the first part of the authorization state, the cryptographic module should authenticatc  
itself to the client software by a challenge-response protocol. The cryptographic module and the  
30 client software share a public cryptography key pair that preestablishes a condition of trust. The  
cryptographic module keeps the private key, and a copy of the corresponding public key is  
embedded in the client software. The client software generates a random number as a challenge  
message and sends it as cleartext to the cryptographic module. The cryptographic module  
responds by signing the received challenge with its private key and returns the resulting  
35 ciphertext to the client software. Using the public key, the client software signs the challenge  
message it had sent and compares it to the cryptographic module's signature of the same  
challenge message received from the cryptographic module. If the signed messages compare, the  
cryptographic module is authenticated.

1       Once the cryptographic module is authenticated, the client software generates a HMK and prompts the user for a password. The client software then encrypts both the HMK and the user's password with its public Key, and sends this ciphertext to the cryptographic module. The user's name is also sent in clear text to the Postal Server. The cryptographic module uses its private  
5       RSA key to decrypt the password and the HMK. The PSD now has both the HMK and the user's password. This information is associated with the user's name and is cryptographically stored in the database.

      With the success of the authorization state, the client software not only trusts the cryptographic module, but also shares a common HMK with the cryptographic module, which  
10       it uses to sign and challenge each successive message. FIG. 7 illustrates client software and cryptographic module (PSD) 52 communication during the operational state. Client software 53 sends a new challenge message to cryptographic module 52, as shown by 81. The cryptographic module response by signing the challenge with the shared HMK and then sends this ciphertext back to the client software, along with its own challenge, as shown by 82. Client software 53  
15       compares the ciphertext of the challenge it originally sent to the cryptographic module, and also signs the message received from the cryptographic module. If the signatures compare, the client software trusts the cryptographic module for this transaction. Client software 53 uses the cryptographic module challenge message to authenticate itself to cryptographic module 52.

      Client software 53 now sends the signed challenge that cryptographic module 52 had sent, with the addition of the client software local record of the user's ascending and descending registers, as shown by 83. (The ascending register records the amount of postage that is dispensed or printed on each transaction and the descending register records the value or amount of postage that may be dispensed and decreases from an original or charged amount as postage is printed.)

25       The client software also sends a cleartext of the challenge and the transaction message, as shown by 84. Next, the client software sends a Hash Message Authentication Code (HMAC) for all of the data sent in 83 and 84, using shared HMK, as shown by 85. HMAC is a digital signature created using a hash algorithm with an arbitrary message and the secret key (HMK). The client software sends the original arbitrary message and the HMAC to Postal Server via the  
30       network. HMK, as the HMAC Key, stays in the client software 53. The cryptographic module 52 already has a copy of HMK because it was sent over to Postal Server during the user registration process. In another embodiment, Data Encryption Standard Message Authentication Code (DES MAC) is used instead of HMAC.

      Once 83, 84, and 85 are received by cryptographic module 52, the cryptographic module  
35       verifies that the client software's response is identical with its local calculation of the same. This ensures that the message was not tampered with during transit. The cryptographic module then verifies the challenge it received from the client software, in fact, the challenge the cryptographic

1 module had sent to the client software. This authenticates the client software to the cryptographic module.

5 Next, the cryptographic module verifies that the record of the ascending and descending registers that the client software sent is identical to the cryptographic module's local record of the same registers. This ensures that the client software's record of postage available and postage printed matches the cryptographic module's record. Upon a successful verification of the above, the cryptographic module performs the transaction (as shown by 86) and then sends a new challenge to the client software, for the next round of authentication.

10 In one embodiment, the checkpoint concept operates in the following manner. Each module retains in its memory records relating to the three most recent transactions that modified a PSD package. For example, these records include the following data items:

- PSD meter ID
- Transaction type
- Transaction amount
- 15 • PSD AR value
- PSD DR value
- Module serial number
- Date/time stamp (for record replay detection)
- Module total amount reset
- 20 • Module total amount printed
- Module total amount refunded

25 The record of the most recent transaction is also output to the database and is protected from modification by a DES MAC generated using the key HMK\_chkpt. When a PSD transaction is to be performed, the checkpoint record from the database is input along with the PSD package for the meter. Preferably, all IBIP commands to the modules are handled by the function sdx\_dispatch. Within dispatch, the checkpoint record from the database is compared with the most recent checkpoint record stored in the module memory. If they match, it is highly likely that no switchover of the database (resulting in lost records) has occurred. The module then trusts that the PSD package is up to date and allows the IBIP command to be executed.

30 When the IBIP command is completed, the checkpoint record is updated and output to the server for database storage along with the updated PSD package.

In the case of create indicium commands, the server first confirms that the updated records have been stored on the database before the indicium is transmitted to the client for printing. (Server transaction logs keep a record of all messages sent to clients.) In the case of

35 the provider commanding postage value download or create refund indicium, the server reports an error if the database fails to correctly store the updated checkpoint record and PSD package.

If the comparison of internal and external checkpoint records does not match, the module will not execute the IBIP command and an error code is returned to the server. The server then

1 sends a command called "Auto-Recover module Checkpoint" to the module. This command allows a controlled rollback to an older checkpoint if the external checkpoint record matches either of the two older checkpoint records stored in the module internal memory. The module updates its internal records using data from the accepted checkpoint and outputs audit log records  
5 to document the more recent PSD transactions that are to be discarded (transactions more recent than the accepted checkpoint). If none of the module's internal checkpoint records match the record input from the database, auto-recovery fails and an error is returned to the server. This module is now effectively inhibited from processing PSD packages and operator intervention, using the disaster recovery process, is needed to return it to operation.

10 In summary, the checkpoint validation and auto-recovery processes allows the module to verify that the database providing records is up to date and to automatically re-synchronize the module with the database if possible.

The next level of security is achieved by encrypting all communications between the client and the Postal Server subsystem. The encryption-decryption function is employed using  
15 an encryption algorithm, for example, RSA public key encryption algorithm. The client has a unique public and private key pair generated by the Postal Server subsystem that is embedded in the client software and these keys are used for encrypting/decrypting communications between the client and the Postal Server subsystem.

The user secret key (HMK) is further encrypted by using the public key of the  
20 cryptographic module 52 shown in FIGs. 3 and 6. HMK gets encrypted with its PSD encryption keys (3DES) by the cryptographic module 52. Then, the encrypted HMK is stored in the Database subsystem 51 along with other PSD information. In one embodiment, the cryptographic module 52 is embedded in the hardware where Postal Server 41 is running. The Postal Server 41 is connected to the Public Network 73. The cryptographic module 52 is used to decrypt the  
25 encrypted secret key of the user that is stored in the Database subsystem. The user authenticates itself with every request by digitally signing every request using the secret HMK. The cryptographic module 52 verifies the user signature using its copy of HMK stored in the Database subsystem 51.

The interaction between the cryptographic modules and the Database subsystem provides  
30 two more levels of security. The first level of security is the cryptographic module verifying last transactions with the Database subsystem and the second level of security is the cryptographic protection of internal storage registers in the cryptographic modules. In one embodiment, the cryptographic modules store up to five transactions in a respective internal register. The number of transactions compared in the verification process system may be set by the system  
35 administrator. A verification process compares a predetermined number of last transactions. The database subsystem stores a table that preferably includes the cryptographic module(s) present in the Postal Server subsystem 41, the cryptographic module serial numbers, the time of the last transaction the cryptographic module processed, the date of the last

transaction the cryptographic module processed and the value of the last transaction the cryptographic module processed. Other values related to a transaction and a cryptographic module can also be saved for verification purposes. An example of the cryptographic module table, where the Postal Server subsystem has four cryptographic modules, is illustrated below.

Cryptographic module	Cryptographic module Serial. #	Transaction Time	Transaction Date	Transaction Value
1	34576590	11:53 PM	08/06/99	\$ 0.33
2	34582152	07:30 AM	08/05/99	\$ 7.55
3	34593104	03:00 PM	08/02/99	\$ 3.45
4	34593992	11:22 AM	08/03/99	\$ 5.78

When a cryptographic module 52 loads a new PSD out of the Database subsystem 51 (performing a transaction), the cryptographic module's register, containing the last transaction's time, date and value, is verified against that cryptographic module's entry in the Database subsystem's cryptographic module table. The time, date or value for each transaction stored in each cryptographic module should match the corresponding values for the respective cryptographic module stored in the database for the verification process to be successfully completed.

Cryptographic modules do not load new PSD transactions unless the verification process has been successfully completed. If any of the compared values is found to be different, preferably the whole system shuts down until authorized personnel can investigate the situation. In one embodiment, the threshold in the system is adjustable so that the system may be set to shut down if one, two or more cryptographic modules fail the verification process. The registers of each cryptographic module are cryptographically protected against any unauthorized access of the database. This provides another level of security.

Additionally, the Database subsystem for the on-line VBI system is designed to allow for easy recovery from minor or major failures. A dual redundancy (backup) database server is connected to the on-line VBI system to mitigate the damage caused by the failure of the primary database server. In one embodiment, a backup database automatically carries all of the responsibilities of the primary Database server until the primary database server is repaired. Preferably, the Database subsystem is monitored 24 hours a day to immediately recognize problems.

In order to maintain data protection in case of media failure, software error (system crash), or power outage, a cryptographically protected transaction log on the primary database server is off-loaded to tape periodically throughout the day. The transaction log does not need



1 to be a real time backup, but the number of transactions lost would be minimized since the backup occurs periodically throughout the day.

5 In addition, on a daily basis, the data in the Database subsystem is backed up to a backup system, such as a tape backup system, and stored off premises in a secure facility. After the daily backup is completed, a transaction log of the primary database server is backed up to a backup system, such as a tape drive, and stored off premises in a secure facility with the data backup of the database subsystem.

10 Minor failures of the primary database subsystem, for example media failure, power outages and software error, are easily handled in the on-line VBI system. In one embodiment, to change from the backup Database server in the case of the failure of the primary database server, the system administrator changes the IP address to that of the backup database server and makes the primary database server the backup database server. Next, the system administrator resets the database server and loads the latest encrypted transaction log. The system administrator uses a cryptographic module to decrypt the transaction log and the decrypted information from the transaction log is loaded into the Database subsystem.

15 In the case of catastrophic failure, e.g. loss of the database and the cryptographic modules, as long as the transaction log and daily backups are stored off premises, the data can be recovered. The data is recovered by storing a cryptographic module in an off-site secure location close to the stored transaction logs, daily backups and backup on-line VBI system. The backup of the system is combined with the transaction log to reinstate all of the accounts contained in the transaction log.

20 In one embodiment of the invention, the daily backups and the transaction logs are downloaded to a tape. If a catastrophic failure occurs, then the latest daily backup tape is loaded onto the backup on-line VBI system. Next, the cryptographic module decrypts the backup tape and the decrypted information from the backup tape is loaded into the Database subsystem. Then, the cryptographic module decrypts the transaction log and the decrypted information from the transaction log is loaded into the Database subsystem.

25 Preferably, the verification process that the cryptographic module performs with the cryptographic module table in the Database subsystem is not performed, because the new cryptographic module does not have any record of previous transactions, since it was sitting in a vault off premises from the on-line VBI system. The transaction log is cryptographically protected so that unauthorized personnel cannot manipulate the data.

30 The cryptographic module is able to trust the cryptographically protected data of the transaction log because cryptographic module has knowledge of the format of the transaction log. As a result, the entire database is recovered and recreated by at least one cryptographic module using the last transaction log and the backup data.

35 It will be recognized by those skilled in the art that various modifications may be made to the illustrated and other embodiments of the invention described above, without departing

1 from the broad inventive scope thereof. It will be understood therefore that the invention is not  
limited to the particular embodiments or arrangements disclosed, but is rather intended to cover  
any changes, adaptations or modifications which are within the scope and spirit of the invention  
as defined by the appended claims.

5

10

15

20

25

30

35

## 1 WHAT IS CLAIMED IS:

- 5       1.     A scalable on-line system for printing value bearing items (VBI) comprising:  
a client system for interfacing with one or more users; and  
a scalable server system capable of communicating with the client system over a  
communication network comprising:  
a database remote from the users including information about the users;  
a stateless cryptographic module for authenticating the one or more users; and  
a plurality of security device transaction data stored in the database for ensuring  
10    authenticity of the one or more users, wherein each security device transaction data can be  
processed in the server system in a stateless manner.
- 15       2.     The system of claim 1, wherein each security device transaction data is related to  
a user.
3.     The system of claim 2, wherein the security device transaction data related to a  
user is loaded into the cryptographic module when the user requests to operate on a value bearing  
item.
- 20       4.     The system of claim 3, wherein the security device transaction data related to a  
user is updated and returned to the database.
5.     The system of claim 1, further comprising at least one more stateless  
cryptographic module, wherein each cryptographic module is capable of processing any of the  
25    plurality of security device transaction data.
6.     The system of claim 5, wherein a user can be authenticated using any of the  
cryptographic modules.
- 30       7.     The system of claim 5, further comprising computer executable code for load-  
balancing to route user requests to the at least one more cryptographic module.
8.     The system of claim 5, further comprising computer executable code for load-  
balancing to distribute traffic among the multiple cryptographic modules.
- 35       9.     The system of claim 1, wherein the cryptographic module is capable of  
authenticating any of the one or more users.

1           10.     The system of claim 1, wherein the database is partitioned across a plurality of  
physical databases.

5           11.     The system of claim 1, wherein the cryptographic module performs cryptographic  
function on a transaction related to the database.

          12.     The system of claim 1, further comprising computer executable code for password  
authentication to prevent unauthorized access to the database.

10          13.     The system of claim 1, wherein the database stores a first set of one or more last  
database transactions and the cryptographic module stores a second set of one or more last  
database transactions for comparison with the first set of one or more last database transactions  
stored in the database to verify each database transaction.

15          14.     The system of claim 13, wherein the cryptographic module prevents further  
database transactions if the second set of one or more last transaction stored in the cryptographic  
module does not compare with the first set of one or more last transaction stored in the database.

20          15.     The system of claim 1, wherein the cryptographic module includes a data  
validation subsystem for allowing the module to verify that data is up to date and an auto-  
recovery subsystem for automatically re-synchronize the module with the data.

          16.     The system of claim 1, wherein the cryptographic module includes a computer  
executable code for preventing unauthorized modification of data.

25          17.     The system of claim 1, wherein the cryptographic module includes a computer  
executable code for ensuring the proper operation of cryptographic security and VBI related  
meter functions.

30          18.     The system of claim 1, wherein the cryptographic module includes a computer  
executable code for supporting multiple concurrent users.

          19.     The system of claim 1, wherein the database includes one or more indicium data  
elements, data for account maintenance, and data for revenue protection.

35          20.     The system of claim 1, wherein the database includes virtual meter information.

          21.     The system of claim 1, wherein the database includes descending register data.

- 1           22.    The system of claim 1, wherein the value bearing item is a mail piece.
23.    The system of claim 22, wherein the postal indicium comprises a digital signature.
- 5           24.    The system of claim 1, wherein the cryptographic module performs cryptographic function on validation information according to a user request for printing a VBI.
25.    The system of claim 1, wherein the cryptographic module generates data sufficient to print a postal indicium in compliance with postal service regulation on a mail piece.
- 10           26.    The system of claim 1, wherein the value bearing item is a ticket.
27.    The system of claim 1, wherein a bar code is printed on the value bearing item.
- 15           28.    The system of claim 1, wherein the value bearing item is a coupon.
29.    The system of claim 1, wherein the value bearing item is currency.
30.    The system of claim 1, wherein the value bearing item is a voucher.
- 20           31.    The system of claim 1, wherein the value bearing item is a traveler's check.
32.    The system of claim 1, wherein each security device transaction data includes one or more of an ascending register value, a descending register value, a respective cryptographic module ID, an indicium key certificate serial number, a licensing ZIP code, a key token for an indicium signing key, user secrets, a key for encrypting user secrets, date and time of last transaction, last challenge received from a respective client subsystem, an operational state of the respective module, expiration dates for keys, and a passphrase repetition list.
- 25           33.    The system of claim 1, wherein each security device transaction data includes one or more of a private key, a public key, and a public key certificate, wherein the private key is used to sign module status responses and a VBI which, in conjunction with a public key certificate, demonstrates that the module and the VBI are authentic.
- 30           34.    The system of claim 1, wherein the cryptographic module is capable of performing one or more of Rivest, Shamir and Adleman (RSA) public key encryption, DES, Triple-DES, DSA signature, SHA-1, and Pseudo-random number generation algorithms.
- 35

1           35.    The system of claim 1, wherein the server system further comprises one or more  
of a postal server subsystem, a provider server subsystem, an e-commerce subsystem, a staging  
subsystem, a client support subsystem, a decision support subsystem, a SMTP subsystem, an  
address matching service subsystem, a SSL proxy server subsystem, and a web server subsystem.

5           36.    The system of claim 1, wherein the database includes one or more of a postal  
database, a provider database, an e-commerce database, and a membership database.

10          37.    The system of claim 1, further comprising an address matching server for  
verifying a correct address specified by a user.

          38.    The system of claim 1, further comprising a printer driver database for storing  
supported printer driver information.

15          39.    A method for printing value-bearing items (VBI) via a communication network  
including a client system, and a scalable server system, the method comprising the steps of:  
interfacing with one or more users via the client system;  
communicating with the client system over the communication network;  
storing user information in a database accessible through the network;  
20          authenticating the one or more users using a scalable cryptographic module; and  
storing in the database a plurality of security device transaction data for ensuring  
authenticity of the one or more users, wherein each security device transaction data can be  
processed in the server system in a stateless manner.

25          40.    The method of claim 39, wherein each security device transaction data is related  
to a user.

          41.    The method of claim 40, further comprising the step of loading the security device  
transaction data related to a user into the cryptographic module when the user requests to operate  
30          on a value bearing item.

          42.    The method of claim 41, further comprising the steps of updating and returning  
the security device transaction data related to a user to the database.

35          43.    The method of claim 39, further comprising the step of adding at least one more  
stateless cryptographic module, wherein each cryptographic module is capable of processing any  
of the plurality of security device transaction data.

1           44.    The method of claim 39, further comprising the step of authenticating a user using  
any of the cryptographic modules.

5           45.    The method of claim 43, further comprising the step of load-balancing to route  
user requests to the at least one more cryptographic module.

          46.    The method of claim 43, further comprising the step of load-balancing to  
distribute traffic among the multiple cryptographic modules.

10          47.    The method of claim 39, further comprising the step of the authenticating any of  
the one or more users using the cryptographic module.

          48.    The system of claim 1, further comprising the step of partitioning the database  
across a plurality of physical databases.

15          49.    The method of claim 39, further comprising the step of encrypting database  
transactions using the cryptographic module.

          50.    The method of claim 39, further comprising the steps of     verifying a user  
password before granting access to the database.

20          51.    The method of claim 39, further comprising the steps of  
storing one or more last database transactions in the database;  
storing one or more last database transactions in the cryptographic module; and  
comparing the one or more last database transactions stored in the database with the one  
25 or more last database transactions stored in the cryptographic module to verify each database  
transaction.

          52.    The method of claim 39, further comprising the step of encrypting transactions  
related to the database using the cryptographic module.

30          53.    The method of claim 39, further comprising the steps of storing one or more last  
database transactions in the database, storing one or more last database transactions in the  
cryptographic module for comparison with the one or more last database transactions stored in  
the database to verify each database transaction.

35          54.    The method of claim 53, further comprising the step of preventing further database  
transactions if the one or more last transaction stored in the cryptographic module does not  
compare with the one or more last transaction stored in the database.

1           55.    The method of claim 39, further comprising the steps of preventing unauthorized  
modification of data using the cryptographic module.

5           56.    The method of claim 39, further comprising the steps of verifying that the  
database is up to date.

          57.    The method of claim 39, further comprising the steps of automatically re-  
synchronizing the cryptographic module with the database.

10          58.    The method of claim 39, further comprising the step of ensuring the proper  
operation of cryptographic security and VBI related meter functions.

          59.    The method of claim 39, further comprising the steps of supporting multiple  
concurrent operators.

15          60.    The method of claim 39, further comprising the steps of:  
                storing information about a number of last transactions in a respective internal  
                register of each of the one or more cryptographic devices;  
                storing a table including the information about a last transaction in the database;  
20                comparing the information saved in the respective device with the respective  
information saved in the database; and  
                loading a new transaction data if the respective information stored in the device  
compares with the respective information stored in the database.

25          61.    The method of claim 39, further comprising the step of storing data for creating  
one or more indicium, account maintenance, and revenue protection.

          62.    The method of claim 39, further comprising the step of printing a mail piece.

30          63.    The method of claim 62, wherein the mail piece includes a digital signature.

          64.    The method of claim 62, wherein the mail piece includes a postage amount.

35          65.    The method of claim 62, wherein the mail piece includes an ascending register of  
used postage and descending register of available postage.

          66.    The method of claim 50, further comprising the step of printing a ticket.



1 67. The method of claim 39, further comprising the step of printing a bar code.

68. The method of claim 39, further comprising the step of printing a coupon.

5 69. The method of claim 39, further comprising the step of printing currency.

70. The method of claim 39, further comprising the step of printing a voucher.

10 71. The method of claim 39, further comprising the step of printing a traveler's check.

72. The method of claim 39, wherein the security device transaction data includes an ascending register value, a descending register value, a respective cryptographic device ID, an indicium key certificate serial number, a licensing ZIP code, a key token for an indicium signing key, user secrets, a key for encrypting user secrets, date and time of last transaction, last challenge received from a respective client subsystem, an operational state of the respective device, expiration dates for keys, and a passphrase repetition list.

15 73. The method of claim 39, further comprising the step of performing one or more of Rivest, Shamir and Adleman (RSA) public key encryption, DES, Triple-DES, DSA signature, SHA-1, and Pseudo-random number generation algorithms using each of the cryptographic devices.

20 74. The method of claim 39, further comprising the step keeping track of user accesses to a vendor website using a website database.

25 75. The method of claim 39, further comprising the step of storing postal transaction data, financial transaction data, customer marketing information, commerce product information, meter license information, meter resets, meter history, and meter movement information in an offline database.

30 76. The method of claim 39, further comprising the step of storing customer information, financial transactions, and information for marketing queries in a data warehouse database.

35 77. The method of claim 39, further comprising the steps of authorizing and capturing funds from a customer's account and transferring the funds to a vendor's account using an e-commerce server.

1           78.    The method of claim 39, further comprising the step of verifying a correct address  
specified using a user using an address matching server.

5           79.    The method of claim 39, further comprising the step of storing supported printer  
driver information in a printer driver database.

10

15


20

25

30


35

FIG. 1




2/8

FIG. 2




3/8


FIG. 3



4/8

FIG. 4





6/8

FIG. 5






FIG. 6





FIG. 7



# INTERNATIONAL SEARCH REPORT

Int. Patent Application No.

PCT/US 00/41201

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 G07B17/00

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G07B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 927 958 A (PITNEY BOWES) 7 July 1999 (1999-07-07)	1-73, 75-79
Y	claim 1; figure 1	74
Y	WO 99 18514 A (CONTACT DYNAMICS INC) 15 April 1999 (1999-04-15)	74
A	claim 1	
A	EP 0 948 158 A (FRANCOTYP POSTALIA GMBH) 6 October 1999 (1999-10-06)	1-79
A	claim 1; figure 2	
A	EP 0 927 963 A (PITNEY BOWES) 7 July 1999 (1999-07-07)	1-79
A	claim 1; figure 1	
	-/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*&\* document member of the same patent family

Date of the actual completion of the international search

15 February 2001

Date of mailing of the international search report

23/02/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl  
Fax: (+31-70) 340-3016

Authorized officer

Kirsten, K

# INTERNATIONAL SEARCH REPORT

Int. J. Appl. No.

PCT/US 00/41201

C(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98 57302 A (RAHRIG JOHN G ;RILEY DAVID W (US); GRAVELL LINDA V (US); PINTSOV L) 17 December 1998 (1998-12-17) claim 1; figure 1	1-79
A	US 4 802 218 A (BRISTOW STEPHEN ET AL) 31 January 1989 (1989-01-31) claim 1; figure 3	1-79
A	EP 0 840 258 A (PITNEY BOWES) 6 May 1998 (1998-05-06) claim 1; figure 1	1-79
A	US 4 935 961 A (GARGIULO JOSEPH L ET AL) 19 June 1990 (1990-06-19) claim 1; figure 5	1-79
A	WO 94 27258 A (SPAULDING JOHN ;INTERACTIVE TELEVISION SYSTEMS (US); RHOADES DONAL) 24 November 1994 (1994-11-24) claim 1; figure 1	1-79
A	USPS: "IBIP Postal Security Device Specification" USPS IBIP, 13 June 1996 (1996-06-13), XP002137734 the whole document	1-79

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/41201

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0927958 A	07-07-1999	US 6151591 A	21-11-2000
		AU 9719598 A	08-07-1999
		BR 9806686 A	03-10-2000
		CN 1232234 A	20-10-1999
		JP 11288474 A	19-10-1999
WO 9918514 A	15-04-1999	AU 9793798 A	27-04-1999
		EP 1021770 A	26-07-2000
EP 0948158 A	06-10-1999	DE 19816344 A	07-10-1999
EP 0927963 A	07-07-1999	US 6064993 A	16-05-2000
		AU 9717298 A	08-07-1999
		BR 9805459 A	23-11-1999
		CN 1220431 A	23-06-1999
		JP 2000105845 A	11-04-2000
WO 9857302 A	17-12-1998	AU 7961998 A	30-12-1998
		AU 7963898 A	30-12-1998
		AU 8255898 A	30-12-1998
		AU 8256698 A	30-12-1998
		AU 8567098 A	30-12-1998
		AU 8567298 A	30-12-1998
		BR 9805995 A	31-08-1999
		BR 9806225 A	21-03-2000
		CN 1234890 T	10-11-1999
		CN 1234891 T	10-11-1999
		EP 0925558 A	30-06-1999
		EP 0931299 A	28-07-1999
		EP 0925663 A	30-06-1999
		EP 0920679 A	09-06-1999
		EP 0966728 A	29-12-1999
		EP 0960394 A	01-12-1999
		WO 9857303 A	17-12-1998
		WO 9857460 A	17-12-1998
		WO 9857304 A	17-12-1998
		WO 9857305 A	17-12-1998
		WO 9857306 A	17-12-1998
US 4802218 A	31-01-1989	AT 116778 T	15-01-1995
		AT 175512 T	15-01-1999
		AT 160456 T	15-12-1997
		AT 160039 T	15-11-1997
		AU 605443 B	10-01-1991
		AU 7961287 A	24-03-1988
		BR 8707450 A	06-12-1988
		CA 1320578 A	20-07-1993
		CA 1326911 A	08-02-1994
		CA 1335839 A	06-06-1995
		CA 1296809 A	03-03-1992
		DE 3750958 D	16-02-1995
		DE 3750958 T	08-06-1995
		DE 3752138 D	11-12-1997
		DE 3752138 T	26-03-1998
		DE 3752146 D	02-01-1998
		DE 3752146 T	09-04-1998
		DE 3752247 D	18-02-1999
		DE 3752247 T	10-06-1999

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. Application No

PCT/US 00/41201

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4802218 A		DK 228888 A	17-06-1988
		EP 0294397 A	14-12-1988
		EP 0619563 A	12-10-1994
		EP 0619564 A	12-10-1994
		EP 0619565 A	12-10-1994
		EP 0740275 A	30-10-1996
		FI 882047 A,B,	02-05-1988
		JP 1500863 T	23-03-1989
		JP 2661932 B	08-10-1997
		NO 300660 B	30-06-1997
		WO 8801818 A	10-03-1988
		US 4864618 A	05-09-1989
		US 4900904 A	13-02-1990
		US 4900903 A	13-02-1990
EP 0840258 A	06-05-1998	US 5805701 A	08-09-1998
		CA 2219857 A	01-05-1998
US 4935961 A	19-06-1990	NONE	
WO 9427258 A	24-11-1994	AU 6912894 A	12-12-1994